

# Specifications

## Sunstream SunLift™

SunLift Model	SL2006AR	SL2008AR	SL3010	SL4010AR	SL6012AR	SL8012ER	SL10014ER	SL12018ER	SL18020ER	SL24022ER
Capacity (pounds)	2,000	2,000	3,000	4,000	6,000	8,000	10,000	12,000	18,000	24,000
Lifting Ranges*	<u>36"/48"/60"</u>	<u>36"/48"/60"</u>	<u>48"</u>	<u>36"/48"/60"/(72"*)</u>	<u>36"/48"/60"/(72"*)</u>	<u>60"/(72"*)</u>	<u>60"/(72"*)</u>	<u>60"/(72"*)</u>	<u>60"/(72"*)</u>	<u>60"/(72"*)</u>
Capacity at Max. Lifting Range	1,800	1,800	3,000	4,000	4,500	8,000	9,500	9,500	14,250	19,000
Bunk Length	6'	8'	10'	10'	12'	12'	14'	18'	20'	22'
Frame Length	95"	95"	10'5"	10'5"	12'5"	12'5"	14'5"	18'5"	20'5"	24'
Frame Width	5'6"	5'6"	9'6"	9'6"	10'	11'	11'	11'	12'6"	12'6"
Weight (pounds)	200	210	450	550	655	1,000	1,050	1,500	2,000	2,500
Lifting Speed (Typ.)	15 sec	15 sec	15 sec	25 sec	35 sec	50 sec	50 sec	50 sec	55 sec	60 sec
Min. Water Depth Required (Typ.)	18"	18"	23"	25"	27"	36"	40"	44"	50"	62"
Min. Depth w/Shallow Water Roller (Typ.)	N/A	N/A	N/A	16"	17"	30"	34"	38"	N/A	N/A
Remote Control	Opt.	Opt.	Opt.	Std.	Std.	Std.	Std.	Std.	Std.	Std.
Leg Lengths Available	2'-12'	2'-12'	2'-16'	2'-16'	2'-16'	2'-16'	2'-16'	2'-16'	2'-16'	2'-16'

\*Some lifting ranges require optional leg extensions. Standard ranges are shown with underline (example: 36").

\*\* Special Order Model XR 72" Range.

## Sunstream FloatLift™

FloatLift Model	FL6012	FL10014	FL13018	FL13018W
Capacity (pounds)	6,000	10,500	13,000	13,000
Bunk Length	12'	14'	18'	18'
Lift Length	20'	24'	29'	29'
Lift Width UP Position	10'6"	11'11"	11'11"	13'4"
Weight (pounds)	1,300	2,500	2,900	3,100
Launching Speed (Typ.)	18 sec	18 sec	40 sec	40 sec
Water Depth Required	draft + 12"	draft + 12"	draft + 12"	draft + 12"
Remote	Std.	Std.	Std.	Std.
Minimum Slip Width	12'	14'*	14'*	16'*
Maximum Boat Beam	8'6"	10'6"	10'6"	12'

\* Wider slip required for beams over 9'6".

## Sunstream **Small Craft Lifts**

### DockJock Models DJ1000A4 DJ1000A6 DJ1000D4 DJ1000D6

Power Source	A/C power	A/C power	D/C power	D/C power
Capacity (pounds)	1,000	1,000	1,000	1,000
Lifting Range	48"	84"	48"	84"
Track Length	72"	96"	72"	96"
Arm Width	40"	40"	40"	40"
Optional Extended Length	60"	60"	60"	60"
Weight (pounds)	121	134	121	134

### SunLift Mini

#### SL2006AR SL2008AR

Capacity (pounds)	2,000	2,000
Lifting Ranges*	36"/48"/60"	36"/48"/60"
Capacity at 48" & 60" Lifting Range (pounds)	1,800	1,800
Bunk Length	6'	8'
Frame Length	95"	95"
Frame Width	5'6"	5'6"
Weight (pounds)	200	210
Lifting Speed (Typ.)	15 sec	15 sec
Min. Water Depth Required (Typ.)	18"	18"
Remote Control	Opt.	Opt.

\*Some lifting ranges require optional leg extensions. Standard range is 36".

Specifications can vary due to several factors.

## Sunstream **Canopies**

### Deluxe Peaked Roof P22108 P24114 P27114 P27126 P30126 P36126 P42126

Length	22'	24'	27'	27'	30'	36'	42'
Width Between Uprights	108"	114"	114"	126"	126"	126"	126"
Cover Material (Std.)	vinyl	vinyl	vinyl	vinyl	vinyl	vinyl	vinyl
High Wind Kit	Opt.	Opt.	Opt.	Opt.	Opt.	Std.	Std.
For SunLift Models	SL3010	SL6012	SL6012	SL8012	SL8012	SL8012	SL8012
	SL4010			SL10014	SL10014	SL10014	SL10014
				SL12018	SL12018	SL12018	SL12018

Larger Deluxe canopies available via special order.

### HoverCover

#### FA-H24108

#### FA-H301126

#### CH24108

Length	24'	30'*	24'
Width Between Uprights	106"	Adj.	108"
Cover Material	canvas	canvas	canvas
Standard Colors	blue	blue	blue
Lift Model	FloatLift FL6012	FloatLift FL10014	SunLift SL3010, SL4010, SL6012
Translating Action	Yes	Yes	N/A

\*36' HoverCover coming 2006.

### Standard Colors

#### Deluxe Peaked Roof

#### HoverCover



tan



grey



green



blue

Other colors available by special order. Actual color may vary.  
Optional Sunbrella fabric is available in many colors.